

Q-EX Control

Compliance and Applications

- ATEX classification: Group II, Category 2, Gas and Dust
- Area classification: Category 2 (Zone 1 and 21)
- Certificate (ATEX): INERIS 10ATEX0035
- Marking: Ex II 2GD Ex d IIB, Ex tD A21

The Q-EX Control is used to control your helideck lighting groups in Zone 1 or Zone 2 areas. The basic functions are implemented by using only high quality branded components. The Q-EX Control can operate 6 groups of 16A each.

Technical Specifications

- Product Code: Q31WM01 / Q31WM02
- Application: Helideck
- Enclosure type: EJB 18
- IP-Index: IP66
- Enclosure: Seawater resistant aluminium
- Dimensions: 28.74" x 20.47" x 8.66" (73 x 52 x 22 cm) (L x W x H)
- Mounting: Wallmount
- Input Voltage: 380 Vac
- Cable: H07RN-F 3x1
- Output Voltage: 230 Vac

Operation

The Q-EX Control has five switches that can be manually switched on and off. In addition to these switches, the Q-EX Control has a factory standard built-in interface that allows remote control (optional). Using remote control allows the Q-EX Control to switch on several groups by a radio controller or any desired interface. In addition to switching on and off groups remotely, the Power Active and Fault light indicators are interfaced to display remotely.



Order Code	Product Code	Configuration Code
→	Q31 WM ..	NA 15 - 10 - 999
Product Name	Q31 Q-Control	
Mounting	WM Wallmount	
Zone	02 Zone 2 01 Zone 1	
Color	NA N/A	
Input Power	15 380 Vac	
Fixed Digit	10 -	
Fixed Digit	999 -	